

ATP Mount

Product: GM- 107 Q

Product Description:

Premium Mounting Tape For the permanent, self-adhesive lamination of even surfaces. Very well processible, provides excellent adhesion to almost all materials like plastics, films, wood, glasses or metals with excellent flatness. Suitable for in- and outdoor application. The product then can be used over a long period of time internally for mounting in galleries, museums and for photography. The film/adhesive combination will not materially affect the image or photograph, due to its pH neutral adhesive (other interferences between ink and photopaper to be checked separately).

Product structure:

Support	PET film, 12 µm, transparent
Interliner	Release paper, special coating, white, 90 g/m ²
Adhesive	pure polyacrylic , permanent, transparent
Total Thickness	0.07 mm
Adhesive weight	60 g/m ²

Characteristics:

		Average Value	Test Method
Adhesion on steel:	(after 20 min.)	8 N/25mm	AFERA 5001
Adhesion on steel:	(after 24 h)	11 N/25mm	AFERA 5001

Application temperature:	min. +10°C
End-Use Temperature range:	from -40°C to +150°C
Shelf life:	2 years (see application information)
Durability:	2 years

The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence. Exposure to extreme conditions (tropical climate, high humidity, high UV-light exposure or polluted areas) can decrease the durability in a dramatically way.

All our products are subjected to a strict quality control by our QM-System. The information is based on our present knowledge and our experience. Because of the large number of possible influences during the processing and application of our products, this information does not release the user from the obligation to conduct his own tests and trials. Users of our products are responsible for observing any patent rights that may exist and for following existing regulations. Our applications technology section is always pleased to give advice about suitability tests on original materials.