

Technical Data Sheet

VISCOM-DIGITAL - Wide Format Ink Jet Print Media

Issue date : 05/01/2005 Date last modification : 29/11/2011

03643 RI-JET 145 GLOSS WHITE AVM REMOVABLE WK135

Face Material

Gloss white monomeric vinyl film.

Type Colour and Finish Weight Thickness Monomeric vinyl Gloss white 107 g/m² ±10% ISO-536 80 µ ±10% ISO 534-80

Adhesive

Removable adhesive offering easy and clean removability from glass and from many other substrates. Not recommended on paper, PVC, ABS, PS, air dried paints and varnishes.

Reference Type Min. Appl. Temp. Service Temp. Shear Tack Final Adhesion AVM removable Acrylic removable +10°C -20°C/+80°C Medium Medium N/inch² Medium N/inch

Liner

Туре	One side siliconised clay coated Kraft	
Colour and Finish Weight	White 135 g/m² ±10%	ISO 536
Thickness Transparency	145 µ ±10% n.a. %	ISO 534 DIN 53 147-64
riansparency	n.a. 70	Birtoo I II ol

Applications

For advertising and promotional applications (window graphics and indoor posters, billboards and signs).

Printing Methods

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **<u>STORAGE CONDITIONS</u>**:

- This material must be stored at a temperature of $~22^\circ\!\!C$ ± $2^\circ\!\!C$ and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A. Via Senatore Simonetta, 24 20867 Caponago (MB) ITALN e-mail:info@ritrama.com w w w . r i t r a m a . c o m

