





Date of issue : 05/01/2005 Last. mod. date : 16/03/2009

**Product code** 

Description

Optically clear double side tape to be used where ultra transparency is required.

Not printable.

This version is offered with one side removable and the other permanent in order to save

03273 ULTRACRYSTALLINE Perm/Remov PP ASR6 removable/ASP 8A permanent

board/print.

For applications on windows, glass, clear boards, etc.

**Technical data** 

## **FACE MATERIAL**

Type Top coated polypropylene

Colour and Finish Clear, gloss Weight 27g/m² Thickness 30 $\mu$ 

**ADHESIVE** 

Reference ASP 8A

Type Acrylic permanent

Min. Appl. Temp. +10°C

 Service Temp.
 -40°C/+140°C

 Shear
 Very high

 Tack FTM9
 15N/inch²

 FinAdh FTM2
 7N/inch

 Reference
 RI-ARS 6

Type Removable acrylic

Min. Appl. Temp. +10°C

Service Temp. -20°C/ +100°C

Shear High
Tack Medium
Ultimate Adhesion Medium

**RELEASE BACKING** 

Type 1 side siliconised polyester

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.