

Technical Data Sheet

Issue date: 11/04/2011 Date last modification: 26/05/2016

# GRAPHICS - PROMOTIONAL

# 08428 RASO WHITE SATIN ACETATE RP1005 PERMANENT WK135

#### Face Material

Gloss white acetate satin fabric with very good opacity.

Type Acetate satin fabric Colour and Finish White

Weight 120 g/m†-10% ISO-536 Thickness 140 -10% ISO 534-80

### Adhesive

Rubber based very aggressive permanent adhesive featuring excellent tack on extremely difficult substrates, especially on apolar materials (like PE and PP).

Reference RP1005

Type Rubber permanent

Min. Appl. Temp. +5 C Service Temp. -30 C/+50 C

Service Temp. -30 C/+50 C Shear Medium

Tack21 N/25mmFINAT FTM9Final Adhesion15 N/25mmFINAT FTM2

This adhesive complies with FDA 175.105.

#### Liner

Type One side siliconised clay coated

Kraft

Colour and Finish White

Weight 135 g/m† PP-032 - ISO

**–10%** 536

Thickness 145 –10% ISO 534
Transparency n.a. % DIN 53 147-64

#### **Applications**

Fabrics, shoes, cards, mattress labels and promotional stickers.

## Printing Methods

Printable in solvent based screenprinting. Testing for suitability between media, printers and inks is always recommended prior to use.

#### Shelf life

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of 22 C 2 C and 50 -5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.





